



## Diamond Series - Inverter



### GS-DC128X

---

<b>Total Cooling Capacity (Btu/h)</b>	12000
<b>Effective Power Input PE (W)</b>	1180
<b>Energy Efficiency Ratio EER (Btu/h)/W</b>	9.07
<b>Measured EER (Btu/h)/W</b>	9.28
<b>Test Voltage (V)</b>	198V and 264V
<b>Test Frequency (Hz)</b>	50Hz
<b>Indoor Test Temp (Dry/Wet °C)</b>	32/23
<b>Outdoor Test Temp (Dry/Wet °C)</b>	52/31
<b>Electric Shock Prevention</b>	Class 1
<b>Climate Type</b>	T3
<b>Power Supply</b>	220-240V~/50Hz
<b>T1 Cooling Capacity</b>	3.51kW / 12000 Btu/h

---

<b>T3 Cooling Capacity</b>	3.14kW / 10700 Btu/h
<b>Cooling Running Current (T1/T3)</b>	4.50A   5.20A
<b>Cooling Power Input (T1/T3)</b>	0.96kW   1.18kW
<b>Power Factor</b>	0.98
<b>ACE</b>	2360 kWh/Yr
<b>EER (T1/T3) (Btu/h)/W</b>	12.50 / 9.07
<b>Max Input Current</b>	8.5A
<b>Max Input Power</b>	2.40kW
<b>Max Discharge Pressure</b>	4.3MPa
<b>Max Suction Pressure</b>	1.15MPa
<b>Refrigerant</b>	R410A
<b>Refrigerant Quality</b>	0.75kg
<b>Waterproof Class</b>	IPX4
<b>Net Weight Indoor Unit (kg)</b>	8.5kg
<b>Net Weight Outdoor Unit (kg)</b>	26kg
<b>Gross Weight Indoor Unit (kg)</b>	11kg
<b>Gross Weight Outdoor Unit (kg)</b>	30kg
<b>Rated Power Input PE (E)</b>	1180W
<b>Cooling Power - Effective Power Input PE (W)</b>	1140.2
<b>Rated Cooling Capacity (Btu/h)</b>	10700
<b>Cooling Capacity (Btu/h)</b>	10585.5
<b>Sensible Cooling Capacity (Btu/h)</b>	102838
<b>Latent Cooling Capacity (Btu/h)</b>	301.7
<b>Loading Capacity (40' HC)</b>	214
<b>Compressor Type</b>	Inverter
<b>Compressor MFG</b>	GMCC
<b>Compressor Model</b>	KSN98D64UFZA3