



Diamond Series - Piston



GS-P327X

T1 Cooling Capacity (Btu/h)	30000
Climate Type	T3
T3 EER for Cooling (Btu/h)/W	10.34
Cooling Power (kW)	2.90kW
Cooling Current (A)	11A
Max Input Power (kW)	4.30kW
Max Input Current (A)	21.5A
Air Volume (m3/h)	1600m3/h
Power Supply	220-240V~/50Hz
Max High Pressure (MPa)	3.20MPa
Max Suction Pressure (MPa)	0.8MPa

Inside Noise Level (dB(A))	52dB(A)
Outside Noise Level (dB(A))	60dB(A)
Compressor Type	Reciprocating
Compressor MFG	COPELAND
Compressor Model	CR37K6M-PFZ-101MM
Indoor Unit Dimensions (mm)	1250x360x253
Outdoor Unit Dimensions (mm)	970x805x395
Net Weight Indoor Unit (kg)	16kg
Net Weight Outdoor Unit (kg)	69kg
Gross Weight Indoor Unit (kg)	21kg
Gross Weight Outdoor Unit (kg)	75kg
Electric Shock Prevention	Class I
Waterproof Class Indoor	IPX0
Waterproof Class Outdoor	IPX4
Refrigerant	R22
Charge (kg)	2.05kg
Loading Capacity (40' HC)	98

GS-P377X

T1 Cooling Capacity (Btu/h)	36000
Climate Type	T3
T3 EER for Cooling (Btu/h)/W	10.3
Cooling Power (kW)	3.39kW
Cooling Current (A)	12A
Max Input Power (kW)	4.75kW
Max Input Current (A)	25A
Air Volume (m³/h)	1600m ³ /h
Power Supply	220-240V~/50Hz
Max High Pressure (MPa)	3.20MPa
Max Suction Pressure (MPa)	0.8MPa
Inside Noise Level (dB(A))	52dB(A)
Outside Noise Level (dB(A))	60dB(A)
Compressor Type	Reciprocating
Compressor MFG	COPELAND
Compressor Model	CR42K6M-PFZ-101MM
Indoor Unit Dimensions (mm)	1250x360x253
Outdoor Unit Dimensions (mm)	970x805x395
Net Weight Indoor Unit (kg)	16kg
Net Weight Outdoor Unit (kg)	71kg
Gross Weight Indoor Unit (kg)	21kg
Gross Weight Outdoor Unit (kg)	79kg
Electric Shock Prevention	Class I

Waterproof Class Indoor	IPX0
Waterproof Class Outdoor	IPX4
Refrigerant	R22
Charge (kg)	2.3kg
Loading Capacity (40' HC)	98