



## Floor Standing AC



GS-FS36C

---

<b>Rated T1 Cooling Capacity (Btu/h)</b>	36680
<b>ESMA T3 Cooling Capacity (Btu/h)</b>	32240
<b>Rated Input Cooling (W)</b>	3900
<b>Moisture Removal (L/h)</b>	3.5
<b>Air Circulation (CMH Max)</b>	1600

---

<b>EER For Cooling (W/W)</b>	2.42
<b>Refrigerant (Type/Kg)</b>	R410A
<b>I/U Noise Level Super (dB(A))</b>	51
<b>I/U Noise Level High (dB(A))</b>	49
<b>I/U Noise Level Medium (dB(A))</b>	45
<b>I/U Noise Level Low (dB(A))</b>	42
<b>O/U Noise Level (dB(A))</b>	52
<b>Power Supply - Voltage, Frequency (V,Hz)</b>	220-240V~, 50Hz
<b>Rated Current   Cooling (A)</b>	18.7
<b>LRA (A)</b>	76
<b>Compressor Type</b>	T3 Rotary
<b>Compressor MFG</b>	Hitachi
<b>Compressor Model</b>	ATH356MV-C9EUA
<b>Expansion Device</b>	Throttle valve
<b>Gas Charge (g)</b>	2230
<b>Connecting Pipe Diameter - Liquid Pipe (inch)</b>	3/8
<b>Connecting Pipe Diameter - Gas Pipe (inch)</b>	5/8
<b>Net Dimensions I/U   WxHxD (mm)</b>	580x1870x380
<b>Net Dimensions O/U   WxHxD (mm)</b>	950x1050x340
<b>Net Weight Indoor Unit (Kg)</b>	48
<b>Net Weight Outdoor Unit (Kg)</b>	69
<b>Packing Dimensions I/U   WxHxD (mm)</b>	690x2000x480
<b>Packing Dimensions O/U   WxHxD (mm)</b>	1110x1200x460
<b>Gross Weight Indoor Unit (Kg)</b>	60
<b>Gross Weight Outdoor Unit (Kg)</b>	77
<b>Loading Capacity (40' HC)</b>	52